**Zemo** Partnership

UK BUS Average

ZEB-VOLVO-7900E-2023

Approved Test facility

UTAC

## Zero Emission Bus Certificate

Customer: Vo	olvo Bus Co	rporation			DYNAMOMETER SETTINGS			
Customer Address: De	Dept 86100, ARAK3 S, SE-405 08, Gothenburg		Telematics Capability	Yes	Test Weight	15796	kg	
Test Purpose: Ze	t Purpose: Zero Emission Bus Testing		Maximum Speed (km/h)	80 km/h	F°	789.20	N	
Vehicle Manufacturer: Vo	Manufacturer: Volvo Bus Corporation		Seated Capacity	40	F <sup>1</sup>	6.4041	N/kmh	
Vehicle Model Name: 79	icle Model Name: 7900E		Passenger Capacity	87	F <sup>2</sup>	0.1303	N/kmh <sup>2</sup>	
Powertrain Technology Battery Electric		Declared Unladen Weight (kg)	12095	Equivalent test passengers 21.7		passengers		
Powetrain Configuration Direct Drive		Gross Weight (kg)	19500	Measured Unladen Weight (kg) 13		kg		
Zero Emission Heating He	ero Emission Heating Heat Pump & PTC Heaters		GVW Check OK Number of consecutive tests completed		4	tests		
	Battery Sp	ecification	Charging and Refuellin	g Capability	Hydrogen Specification			
Battery Manufactu	irer	-	Plug Type	CCS 2 & OppCharge	Fuel Cell Manufacturer N/			
Battery Chemistry NMC		Max Charge Capability (kW)	Up to 150kW / 300kW	Fuel Cell Power Rating (kW)		N/A		
Battery Installed Capacity (kWh) 198		Charger Compatibility	DC / OppCharge	Hydrogen Storage Capacity (kg)		N/A		
Battery Usable Capacity (kWh)* 158		Charge time from 20-80% SOC	2 hours	Hydrogen Storage Pressure (bar)		N/A		

\* Recommended manufacturer guideline, subject to warranty

N/A

## Declared fuel, properties and source plus carbon conversion factors

				-	•		
Well-to-Tank Factor:	Electricity	72.65	g CO2e / MJ	Fuel Provider	UK market standard	WTT evidence	DBEIS Conversion 2022
Well-to-Tank Factor:	Hydrogen	N/A	g CO2e / MJ	Capacity of Tanker (kg)	N/A	Fuel Type / Pathway	UK Grid Electricity
Energy Density	Hydrogen	120	MJ / kg	Transport Distance of Hydrogen (km)	N/A	Hydrogen Production Energy Source	UK Grid

E	Emissions and Energy consumption results from approved test facility - Average 4 tests											
Test Phase	HC (g/km)	CO (g/km)	NOx (g/km)	PM (g/km)	CO₂ (g/km)	CH₄ (g/km)*	N₂O (g/km)*	Total Energy Consumption (kWh)	Vehicle Energy Consumption (kWh/km)	Grid Electrical Energy Consumption (kWh/ 100km)		
Outer Urban	N/A	N/A	N/A	N/A	N/A	N/A	N/A	7.93	1.23	143.54		
Inner Urban	N/A	N/A	N/A	N/A	N/A	N/A	N/A	2.79	1.12	131.00		
Rural	N/A	N/A	N/A	N/A	N/A	N/A	N/A	6.88	0.93	109.19		
LBC Average	N/A	N/A	N/A	N/A	N/A	N/A	N/A	10.71	1.20	140.01		

N/A

Zero Emissions (Z.E.) Range: Energy consumption and charging efficiency								
Test Charger Used	22 kW	Total measured energy consumed on vehicle (kWh) <sup>1</sup>	105.55	Max ZE Range at 100% SOC (km)	147			
Hydrogen Energy Over Test (kWh)	N/A	Measured grid energy during charging (kWh)	123.48	Max ZE Range at 80% SOC (km)	118			
Hydrogen Delivered to Vehicle (kg)	N/A	Grid-to-Wheel efficiency (%) <sup>2</sup>	85%	Test Distance Travelled (km)	65			

N/A

N/A

17.59

1.08

126.10

<sup>1</sup> Total measured energy includes energy used during the 23 minute warmup, this is needed for charge efficiency calculation.

N/A

N/A

<sup>2</sup> Grid to Wheel efficiency represents the total energy losses between the grid and the wheels of the bus.

N/A

Calcu	ulated t	Data Generated by (On behalf of Test facility):	Date:			
Test Phase	Fuel Fuel WTT*GHG Emissions (MJ /km) (g CO <sub>2</sub> e / km)		Electrical Energy (MJ / km)	Electricity WTT* GHG Emissions (g CO <sub>2</sub> e / km)		
Outer Urban	N/A	N/A	5.17	375.42	Data Approved by:	Date:
Inner Urban	iral N/A N/A		4.72	342.61		
Rural			3.93	285.58		
LBC Average			5.04	366.19		
UK BUS Average	N/A	N/A	4.54	329.79		

Zero Emission Bus Certificate Summary									
Test Vehicle	Average Euro	VI Diesel Eq	quivalent						
GHG Well-to-Wheel	329.8	g CO2e / km	Average Diesel GHG Equivaler	nt	1300	g CO2e / km			
WTW CO2 per passenger km (@ Max Pass Capacity)	3.8	g CO2e / pass kn	WTW CO2 per passenger km (@ Max Pas	s Capacity)	14.9	g CO2e/pass km			
Overall Zero Emission Bus Performance									
WTW GHG saving	WTW GHG saving 969.7 g CO2e / km			Maximum Theoretical Zero Emission Range (km) 147.0					
% WTW GHG saving	% WTW GHG saving 75% g CO2e / km				Vehicle Energy Consumption (kWh/ km) 1.08				
Approved as Zero Emission Bus? (50	or more)		YES						
* WTT : Well-to-Tank ** TTW : Tank-to-Wheel *** WTW : Well-to Wheel									
COMMENTS: Emission results marked in red are below detection levels.		Heating Requirment	Cell	Lower Saloon	Upper Saloon				
LBC = London Bus Cycle - Inner & Outer Urban phases of UKBC only.	LBC = London Bus Cycle - Inner & Outer Urban phases of UKBC only.			10	17	N/A			
		Average Temperatures across testing (°C)	Average Temperatures across testing (°C) 9.41 16.05						

			Average Temperatures across testing	g (°C)	9.41	16.05	N/A
Test Numbers:	ML02018887 (10-Oct-19), ML	02018888 (10-Oct-19), ML02018889 (10-Oct-1	9), ML02018890 (10-Oct-19), ML02018891 (10-Oct-19), ML02018892 (	0-Oct-19)			
Certificate approved by:	0A	Phil Fletcher	Certificate Approved by:	Tim G	riffen		
On behalf of Bus manufacturer	Phi .	14.04.23	On behalf of DfT / Zemo Partnership	21.03	.2023	in Mpr	$\sim$